Series 4.0 & 6.0 Aluminum Surround Frame

Our aluminum extrusions are made with a blend of recycled aluminum billet here in the USA to ensure quality and performance in every Tradewind aluminum window. Our mechanically fastened and accurately notched corners provide for a durable, strong surround frame with a sleek profile that performs as good as it looks. Our louver jalousie windows are weather-tight with concealed corrosion resistant operating hardware. This is not your typical, old school louver jalousie windows from the 1960s. See it, touch it and experience the difference.

Features:

Solid, Durable Construction
Slim Profile
Frame Depth 4-5/8"
Nail-On or Block Frame Option
4" & 6" Louver Blades
Inside Screen Frame
Quick-Change Blade Clips

Benefits:

Maximum Natural Ventilation
Weather-tight Closure
Easy Cleaning
Save on Energy Cost
Custom-Made to Fit Your Home
Built in Hawaii
Fast Turnaround Time

Surround Frame Finish:Bronze or Satin Anodized Finish (Class I)
White Painted Finish

Valley Isle
WINDOWS & DOORS
Mani's Finest View
808-796-5984

Performance Data: Structural Testing 4" Louver Jalousie, Class R PG 30 Fixed-Class LC PG 25


STANDARD WINDOW SIZING TABLE

ALUMINUM SURROUND (Inside Screen) (net window size, custom sizes available)

Standard Widths for both 4" & 6" Louver Windows:

	L	L	L	L	LL	LL	LL	LLL
NOMINAL	1′6″	2′0″	2'6"	3′0″	4′0″	5′0″	6′0″	9'0"
ACTUAL WIDTH	18 ¹¹ / ₁₆ "	24 ¹¹ / ₁₆ "	3011/16"	36 ¹¹ / ₁₆ "	49"	61"	73"	1095/16"
GLASS SIZE	16"	22"	28"	34"	22"	28"	34"	34"

	l″ Surro ₋ouver ŀ		s .18 86	6" Surro		ts
	Standard Height	# of Blades	Actual Height	Standard Height	# of Blades	Actual Height
Single Operator	1′0″	3	12½″	1′0″	2	12%"
	1′6″	4	15%"	1′6″	3	
		5	191/8"			
	2′0″	6	225/8"	2′0″	4	235/8"
		7	261/8"			
				2′6″	5	291/8"
Double Operators	2'6"	8	295%"			
		9	331/8"			
	3′0″	10	36%"	3′0″	6	34%"
	3'6"	11	401/8"	3'6"	7	401/8"
		12	43%"			
	4′0″	13	47 1/8"	4′0″	8	45%"
		14	50% "		9	511/8"
Triple Operators	4'6"	15	541/8"			
	5′0″	16	57%"	5′0″	10	56%"
		17	61½"		11	621/8"
	5'6"	18	64%"	5'6"	12	675/8"
		19	681/8"			
	6′0″	20	71%"	6′0″	13	731/8"
		21	75 1/8″	6′6″	14	78%"
				7′0″	15	841/8"
Quadruple Operato	rs 6'6"	22	78 %"			



Recommended Rough Opening

Block Frame, add $\frac{1}{4}$ " to actual width and height


Nail-on-Frame, add ½" to actual width and height




Single Louver (L) 211/16"


Double Louver (LL) 5" divided by 2


Triple Louver (LLL) 75/16" divided by 3





WINDOW DETAILS








Series 4.0 & 6.0 Louver Jalousie Strip Hardware

Features:

1½" Aluminum Channels Finish/Colors: Bronze Anodized Satin Anodized White Powdercoat

1½" Vinyl Channel
Colors:
White
Almond

Solid, Durable, Components



1/4" Clips for Glass & Aluminum Blades 3/4" Clips for Aluminum, PVC & Wood Blades Colors: Almond, Black, Gray & White

4" & 6" Louver Jalousie Blades

Quick Change Blade Clips (No need to remove hardware channel)

Louver Jalousie Blade Options:

4" 1/4" Glass Clear, Gray, Bronze Tint, Etched & Low E

1/4" Aluminum White Powdercoat, Satin & Bronze Anodized

3/4" Aluminum White Powdercoat, Bronze Anodized

3/4" PVC White

3/4" Interlock or Tapered Sapele Wood

6" 1/4" Glass Clear, Gray, Bronze Tint, Etched & Low E

1/4" Aluminum Woodgrain

1/4" Tapered Sapele Wood

Benefits:

Enjoy Maximum, Natural Ventilation
Weather-Tight Closure
Corrosion Resistant Components
Easy Cleaning
Manufactured in Hawaii
Fast Turnaround Time







4" TRADEWIND STRIP SIZES	6" TRADEWIND STRIP SIZES		
SINGLE OPERATOR	SINGLE OPERATOR		
11½" 3 Blades	12" 2 Blades		
15" 4 Blades	17½" 3 Blades		
18½" 5 Blades	23" 4 Blades		
22" 6 Blades	28½" 5 Blades		
25½" 7 Blades			
DOUBLE OPERATOR	DOUBLE OPERATOR		
29" 8 Blades	34" 6 Blades		
32½" 9 Blades	39½" 7 Blades		
36" 10 Blades	45" 8 Blades		
39½" 11 Blades	50½" 9 Blades		
43" 12 Blades	56" 10 Blades		
46½" 13 Blades			
50" 14 Blades			
TRIPLE OPERATOR	TRIPLE OPERATOR		
53½" 15 Blades	61½" 11 Blades		
57" 16 Blades	67" 12 Blades		
60½" 17 Blades	72½" 13 Blades		
64" 18 Blades	78" 14 Blades		
67½" 19 Blades	83½" 15 Blades		
71" 20 Blades			
74½" 21 Blades			
FOUR OPERATORS	* 21/8" Deduction for		
78" 22 Blades	Louver Jalousie Blades		



- 1) Before Installing Jalousie Hardware, window operating should be plumb and square.
- 2) Aligning of Hardware in window opening should be positioned so when Jalousie Blades are in the fully opened position they do not interfere with the exterior insect screen.
- 3) After locating the proper position, install the aluminum back plate, (Diagram A) using #8 x 1" PH SMS stainless steel screws to the jambs, making sure both sides are in alignment.
- 4) Install Aluminum Hardware channels with the Jalousie clips in the open position. Snap on channels to the aluminum back plate making sure channels are securely fastened from top to bottom. Use #8 x 1¼" FH SMS at each end of channel.
- 5) To install head and sill weather strips, cut the extruded aluminum stops to the width of the window jamb to jamb. Notch out ¾" of the base (ribbed side) of extrusion from each and leaving the one side to extend past the louver channel and up the window jamb. Use #8 x 1" PH SMS stainless steel screws (Diagram B) to secure the weather strips to the head and sill.

Drill one %6'' diameter hole through upstand containing PVC Weatherseal midway between jambs to drain any moisture on sill.









ur vinyl extrusions are made with 100% virgin vinyl materials here in the USA to ensure quality and performance in the Tradewind window. Our fusion-welded 45 degree mitered corners provides for a durable, strong surround frame with a sleek profile that performs as good as it looks. Our louver jalousie windows are weather-tight with concealed corrosion resistant operating hardware. This is not your old school louver jalousie windows from the 1960s.

See it. Touch it. Experience the difference!

FEATURES

Solid, Durable Construction
Slim Profile
Frame Depth 4-5/8"
Nail-On or Block Frame Option
4" & 6" Louver Blades
Inside & Outside Screen
Frame Options
Quick-Change Blade Clips
Optional Exterior Retro-Fit Trim
Variety of Fixed & Louver
Combinations

BENEFITS

Maximum Natural Ventilation Weather-tight Closure Easy Cleaning Save on Energy Cost Custom Made to fit your Home Built in Hawaii

VINYL SURROUND FRAME FINISH

Almond White



STANDARD WINDOW SIZING TABLE

(net window size, custom sizes available)

Standard Widths for both 4" and 6" VINYL Louver Windows:


			L .	L	L	LL	LL	LL	LLL
NOMINAL WIDTH		1′6″	2′0″	2'6"	3'0"	4'0"	5'0"	6'0"	9'0"
ACTUAL WIDTH	Interior Screens	19 ⁵ / ₁₆ "	25 ⁵ / ₁₆ "	31 ⁵ / ₁₆ "	37 ⁵ / ₁₆ "	50 ³ /8"	62 ³ /8"	74 ³ / ₈ "	111 ⁷ / ₁₆ "
	Exterior Screens	18 ⁷ /8"	24 ⁷ / ₈ "	30 ⁷ / ₈ "	36 ⁷ / ₈ "	487/8"	60 ⁷ /8"	72 ⁷ /8"	108 ³ /16"


	4" VINYL Surround Louver Heights					
	Nominal Height	# of Blades	INSIDE SCREEN Actual Height	OUTSIDE SCREEN Actual Height		
SINGLE OPERATOR	1′0″	3	13"	14¹/₂″		
	1′6″	4	16 ¹ / ₂ "	18"		
		5	20"	21 ¹ / ₂ "		
	2′0″	6	231/2"	25"		
		7	27"	281/2"		
DOUBLE OPERATORS	2′6″	8	301/2"	32"		
		9	34"	35½ ″		
	3′0″	10	37 ½″	39"		
	3'6"	11	41"	421/2"		
		12	441/2"	46"		
	4'0"	13	48"	49 ¹ / ₂ "		
		14	511/2"	53"		
TRIPLE OPERATORS	4'6"	15	55″	56½ ″		
	5′0″	16	58 ½"	60"		
		17	62"	63 ¹ / ₂ "		
	5'6"	18	65 ¹ / ₂ "	67"		
		19	69"	701/2"		
	6′0″	20	72 ¹ / ₂ "	74"		
		21	76″	77 ½"		
FOUR OPERATORS	6'6"	22	79 ½″	81"		


6"	VINYL S	urround Louver	· Heights
Nominal Height	# of Blades	INSIDE SCREEN Actual Height	OUTSIDE SCREEN Actual Height
1′0″		13 ¹ / ₂ "	15"
1′6″		19"	201/2"
2′0″		241/2"	26"
2′6″		30"	311/2"
3′0″		35 ¹ / ₂ "	37"
3′6″		41"	42 ¹ / ₂ "
4′0″		461/2"	48"
4′6″		52"	531/2"
5′0″		57 ¹ / ₂ "	59"
		63"	641/2"
5′6″		68¹/₂ "	70"
6′0″		74"	75 ½"
6'6"		79 ½″	81"
7′0″		85"	86¹/₂"

RECOMMENDED ROUGH OPENING: Block Frame, add 1/4" to actual width and height. Nail-on-Frame, add 1/2" to actual width and height.

WINDOW TYPES







WINDOW DETAILS

